



# International Fireproof Technology Inc.

The Ultimate in Firestop Solutions and Fire Protective Coatings

www.painttoprotect.com

949-975-8588

Facility	Testing Standard	Protocol	Time/Test Results	Coverage Rate
Intertek	ASTM E 84	Surface Burning Characteristics	Flame 25 / Smoke 165	300 sq. ft. per gal
Intertek	ASTM E 84-08 30 minutes extended with exterior top coat	Surface Burning, California Urban Wildland Interface, NFPA 703 Standard for FRTW	Flame 0 / Smoke 20	100 sq. ft. per gal
Applied Physics Laboratory	A.S. 1530 part 3, 1999 Early Fire Hazard Properties	Simultaneous Ignition, Flame Prop., Heat release and Smoke release	0 / 0 / 0 / 3	2.5 sq m/L
Western Fire Center (WFCi)	A.S.1530.4 Equivalent to ASTM E 119, CAN/ULC S 101	Thermal Barrier, Wood Stud 1/2" Gypsum Assembly	1 Hour / Passed	65 sq. ft. per gal
CSIRO	A.S.1530.4 Equivalent to ASTM E 119, CAN/ULC S 101	Thermal Barrier, FC Sheet ceilings	90/90/90 and 60 Minutes RISF	0.7m <sup>2</sup> /L
CSIRO	A.S.1530.4 Equivalent to ASTM E 119, CAN/ULC S 101	Thermal Barrier, Fibrous plaster ceilings	90/90/90 and 60 Minutes RISF	1m <sup>2</sup> /L
CSIRO	A.S.1530.4 Equivalent to ASTM E 119, CAN/ULC S 101	Thermal Barrier, Standard plaster-board ceilings	60/60/60 and 60 Minutes RISF	1m <sup>2</sup> /L
CSIRO	A.S.1530.4 Equivalent to ASTM E 119, CAN/ULC S 101	Thermal Barrier, Lath and plaster ceilings	90/90/90 and 60 Minutes RISF	1m <sup>2</sup> /L
International Carbide	ASTM E 119 Internal Test Report,	Vertical wall 1/2" Stud / Gypsum Assembly	1 Hour / Passed	60 sq. ft. per gal
Intertek	CAN/ULC S101	Fire Endurance Thermal Barrier	15 Minutes / Passed	110 sq. ft. per gal
Intertek	CAN/ULC S102	Surface Burning	Flame 0 / Smoke 25	
Accugen Laboratories Inc.	ASTM D 5590	Mold and Fungal Resistance Test	Mold Resistant	
International Carbide	ASTM E119 Internal Test	Fire Endurance and Hose Stream / Plywood	1 Hour / Passed	40 sq. ft. per gal
Wecks Labs.	EPA AQMD VOC	VOC Emission	56 g/L	
CSIST Fire Research Labs	NES 713	Toxicity During Combustion	Non Toxic	
UL	UL 723	Surface Burning	Flame 5 Smoke 10	100 sq. ft. per gal
UL	UL 723	Surface Burning	Flame 10 Smoke 25	200 sq. ft. per gal

Uses Elementary, Intermediate, High School, Colleges, Nursing Homes, Hospitals, Child Care Centers, Penal Institutions, Apartments, Hotels, Factories, Warehouses, Utilities, Businesses, Retail Stores, Restaurants, Railroad, Other Transportation Companies, Military Installations, Other Government Facilities.